

PVP-1650

SPECIAL FEATURES

- * Application in audio AMP power distributor
- * Stable Output
- * Protection Circuit Built-in
- * Power Factor Correction
- * Built-in inrush current protection
- * Application products for ROHS
- * Built to meet FCC class B : Customer Ready
- * Safety Approved : Customer Ready

ENVIRONMENTAL

- * Operating temperature range 0 to +45 deg.C.
- * Storage temperature range -20 to +70 deg.C.
- * Circuit is coated for protection against humidity



ELECTRICAL SPECIFICATION

1. Input Requirements

- Input Voltage Range : AC 90V ~ 264V
- Input Frequency Range : 47Hz ~ 63Hz
- Input Current Range : < 2.0A

2. Output Requirements

Output Name	Output Typical(V)	Variable Voltage Range(V)	Voltage Tolerance(%)	Output Current(A)	
				Min	Max
5V	5	4.75VDC ~ 5.25VDC	±5	0	1.0
9V	9	8.55VDC ~ 9.45VDC	±5	0	3.0
12VA	12	11.4VDC ~ 12.6VDC	±5	0	3.0
12VB	12	11.4VDC ~ 12.6VDC	±5	0	3.0
12VC	12	11.4VDC ~ 12.6VDC	±5	0	3.0
12VD	12	11.4VDC ~ 12.6VDC	±5	0	3.0

DIMENSION

Size : 223mm X 160mm X 36.6mm

